

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

B11


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : C05F 17/02	A1	(11) International Publication Number: WO 93/16018 (43) International Publication Date: 19 August 1993 (19.08.93)
(21) International Application Number: PCT/FI93/00053 (22) International Filing Date: 17 February 1993 (17.02.93) (30) Priority data: U920149 18 February 1992 (18.02.92) FI 924534 7 October 1992 (07.10.92) FI (71) Applicant (for all designated States except US): FAVORIT OY [FI/FI]; Box 12, SF-27501 Kauttua (FI). (72) Inventor; and (75) Inventor/Applicant (for US only): KARINIEMI, Pekka [FI/FI]; Box 12, SF-27501 Kauttua (FI). (74) Agent: PAPULA REIN LAHTELA OY; Box 981, Salom- onkatu 17 B, SF-00101 Helsinki (FI).	(81) Designated States: AT, AU, BB, BG, BR, CA, CH, CZ, DE, DK, ES, FI, GB, HU, JP, KP, KR, LK, LU, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SK, UA, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, SN, TD, TG). Published With international search report. In English translation (filed in Finnish).	

(54) Title: COMPOST MAKER

(57) Abstract

A compost maker, comprising an upright container (1) having on its top end a cover (2) for introducing material to be composted in the container, having in its lower part a hatch (3) for removing composted material from the container, and containing an air tube system (4) for guiding air in among the material to be composted. The air tube system (4) comprises at least two tubes (5) on different heights, the lower tube being connected through the wall (6) of the container with an air intake aperture (7), and which are interconnected with a connecting tube (8) and their lower parts provided with holes (9). Furthermore, the cover (2) is fitted with an exit duct (10), the air flowing through said holes (9) and upward through the material to be composted and through the exit duct out from the container, while the material to be composted runs, supported by the transverse tubes, in controlled manner downward as the combustion of the material progresses.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SK	Slovak Republic
CI	Côte d'Ivoire	LI	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TG	Togo
DE	Germany	MG	Madagascar	UA	Ukraine
DK	Denmark	ML	Mali	US	United States of America
ES	Spain	MN	Mongolia	VN	Viet Nam
FI	Finland				

WO 93/16018

PCT/FI93/00053

1

COMPOST MAKER

The present invention concerns a compost maker as defined in the preamble to Claim 1.

5 In existing art, various container-like compost maker designs are known in which the material to be composted is introduced through an openable hatch on top, this material flowing downward in the container, and comparatively finished mould being obtained from
10 the lower part of the container. Compost maker designs of this type are disclosed e.g. in following patents: GB 1403984, DE 3802499, and US 4105412.

The greatest problem in present designs is indeterminacy of their air circulation. The containers
15 leak rather great quantities of gas through the hatch joints, and the air passages provided in them direct the air summarily in among the material to be composted, whereby its combustion is uneven and the temperature inside the compost maker varies greatly in accordance with ambient conditions. It is also a fact that
20 the material to be composted flows downward, and is packed, unevenly at different points in the compost maker, resulting in uneven combustion.

The object of the invention is to eliminate
25 the drawbacks just discussed. It is particularly an object of the invention, to disclose a novel compost maker which enables closely controlled and stable conditions within the compost maker so that combustion of the material to be composted takes place uniformly and
30 under substantially constant conditions, independent of conditions external to the compost maker.

Regarding the circumstances characterizing the invention, reference is made to the claims section.

The compost maker of the invention comprises
35 an upright container having on its top end an openable cover for introducing the material to be composted in said container. In the lower part of the container an

WO 93/16018

PCT/FI93/00053

2

openable hatch is provided for removing the composted material from the container, and the container further comprises a system of air tubes for directing air in among the material to be composted residing in the container.

As taught by the invention, the air tube system comprises at least two substantially horizontal tubes extending substantially from one side of the container to the other, within the container. The tubes are at different heights in the container. The lower tube has been connected through the container wall with an air intake aperture, in order to direct air into the container. The substantially horizontal tubes are interconnected by means of a connecting tube, and the undersides of the horizontal tubes carry apertures serving as air flow holes, through which the air admitted into the tubes by a valve can flow into the material to be composted. Furthermore, the cover is fitted with an exit duct through which the air can flow out of the container.

Thus, the essential feature of the invention are at least two transverse air tubes, supporting the material, on different heights. There may, of course, equally be more than two tubes. For instance, in larger containers, always two in parallel in the same plane, and another two tubes in a second plane. In high containers, tubes may also be provided in several planes.

Advantageously, the air intake aperture and/or the exit duct is provided with an adjustable valve, and the cover is fitted with packings and locking means enabling the cover to be hermetically sealed against the respective rims on the container. The air will then be made to flow with the aid of the adjustable valve in controlled and guided manner through the air flow holes of the tubes and upward through the material to be composted, and through the exit valve on the cover, out of the container. At the same time, in the course of its

WO 93/16018

PCT/FI93/00053

3

progressing combustion the material will run downward in guided manner, supported by the transverse tubes, toward the lower part of the container, whence it can be removed through an openable hatch. Being supported
5 by the tubes, the matter that is being composted will not be packed to a compact clump: it stays fluffy and runs with progressing combustion downward, thus enabling thorough combustion to take place and an end product of good quality to be obtained.

10 Advantageously, the openable cover upon the container as well as the openable hatch in the lower part of the container are both provided with conical rim surfaces and the container presents corresponding, conical mating faces, in which case suitable packings
15 are used between the faces, such as rubber gaskets. Moreover, the cover and the hatch carry suitable locking means, clamp bolts or equivalent, whereby these can be hermetically clamped fast to the container and, thus, extra air leakage from or into the container is
20 prevented.

Advantageously, the compost maker is made of a thermally well-insulating structure, e.g. of two plastic/glass fibre shells placed one inside the other and of interposed lagging material, e.g. polyurethane.

25 Advantageously, the transverse tubes are curved, with their ends lower than the centre, i.e., upward convex, whereby in operation, when the tubes get warm and the stuff is pressing down on the tubes, they are placed under stress and push harder against the
30 inner shell of the container and against the supports. In an embodiment of the invention the transverse tubes rest by their ends on an annular support which rests against the inner shell of the container, in which case said annular support and the transverse tubes may in
35 combination constitute air passages through which air can flow into the material to be composted. Thus, advantageously, on the inner shell of the container

WO 93/16018

PCT/FI93/00053

4

bosses or equivalent projections are provided on which the annular support or the transverse tubes rest, implying that they need not be fixedly attached to the inner shell of the container.

5 The compost maker design of the invention affords a chance to create closely controlled and highly stable conditions for combustion, even in a cold environment, notably in instances in which the material used for the container, the cover as well as the hatch
10 is a suitable bilaminar structure, e.g. a suitable plastic with interposed lagging.

In the following the invention is described in detail with reference to the attached drawing, wherein Fig. 1 is a sectional view of a compost maker according
15 to the invention, and Fig. 2 presents an air tube embodiment of the invention.

The compost maker of Fig. 1 consists of an upright, cylindrical container 1, of which the shell is
20 composed of two layers e.g. of glass fibre reinforced plastic with an interposed, suitable lagging, e.g. polyurethane. The upper margins of the container 1 form an outwardly broadening, circular conical surface 13, and the cover 2 of the container carries a mating surface 14 corresponding to this conical surface, whereby
25 the surfaces fit, and become accurately sealed, against each other. Furthermore, in the upper part of the conical surface and the mating surface a gasket 11 has been provided, which seals these surfaces hermetically
30 against each other. The cover 2 is supported by a hinge 15 on the container, whereby when the cover 2 is turned down upon the container the conical surface and the mating surface can be locked in place with the aid of a locking clamp 12 on the side of the cover opposed to
35 the hinge 15.

The cover 2 furthermore carries an exit valve 10, through which the gases can flow out from the con-

WO 93/16018

PCT/FI93/00053

5

5 tainer. The underside surface of the cover 2 has been arranged to have such shape when the cover is closed that it slopes inward from the rim of the container in the downward direction, whereby any moisture condensing on the cover will not run down the sides of the container, but will instead drop down uniformly upon the material to be composted.

10 In the lower part of the container, in the vicinity of its bottom, a draining hatch 3 has been provided, which likewise, in resemblance of the shaping of the cover 2, has conically inward narrowing margins and, on the container, corresponding mating surfaces, between which a gasket 16 is interposed. Hereby, a
15 suitable locking means, which has not been depicted, can be used to secure the hatch 3 tightly in place so that no air leakage is admitted therethrough into the container when the hatch is closed.

The air tube system 4 inside the container 1 consists of two substantially horizontal tubes 5 having
20 oval cross section, which are located at a vertical distance of each other, with 90° offset relative to each other. The tubes are upward curved in the centre and they are interconnected with a vertical connecting tube 8, located substantially in the centre of the container. Both tubes 5 extend inside the container 1 from
25 wall to wall 6 thereof, and they rest on projections 18 on said walls. The lower parts of both tubes 5 are provided with a plurality of air flow holes 9.

Of the tubes 5, the lower one extends at one
30 end through the wall 6 to an adjustable valve 7, and by regulating this valve it becomes possible to control the air flow through the tubes 5 into the container. The container further comprises a thermometer 19, on which the temperature in the container can be read, in
35 accordance with which the valve 7 can be adjusted.

The tubes 5 placed transversely in the container serve as an element supporting the compost mate-

WO 93/16018

PCT/FI93/00053

6

rial, with the effect that the material will not be excessively packed and compacted on the bottom of the container. Since moreover the air flow holes on the tubes have been disposed on their undersides, the holes cannot get plugged, and uniformly functioning air circulation is achieved in the entire material to be composted. The oval cross section configuration of the tubes and their placement with their broad dimension horizontal have been chosen for the reason that this enables the supporting surface and supporting action of the tube to be made comparatively large, and the air flow holes find a good, well-protected accommodation on their underside, which would be clearly less if the tube were round. Moreover, the curved shape of the tubes ensures their holding on support of the projections 18 because at comparatively high temperature, when the stuff is weighing on the tubes, the tubes bend downward and, owing to their curvature, are urged even harder against the sides of the container.

In Fig. 2 is presented an air tube arrangement according to the present invention, in which the transverse tubes 5 of curved shape are braced against each other by a vertical connecting tube 8, and on the ends of the tubes belong annular supports 19, which may equally consist of hollow tubular section material. The support is a substantially horizontal ring running around the inner shell of the container and to which the transverse tube is connected by its ends. Hereby, the supports 19 as well as the tubes 5 will in combination form the air ducts of the compost maker and the structure supporting the stuff being composted, and this entity can be supported as a loose component on the projections 18 on the inner shell, by connecting the air intake hole 20 with the air duct passing through the shell. It is thus understood that the supports 19 may also comprise air holes.

In the foregoing the invention has been de-

WO 93/16018

PCT/FI93/00053

7

scribed by way of example with the aid of an advantageous embodiment thereof, while different structural solutions of the invention are feasible in the scope of the inventive idea delimited by the claims.

WO 93/16018

PCT/FI93/00053

8

CLAIMS

1. A compost maker, comprising an upright container (1),
- 5 - having on its top end an openable cover (2) for introducing material to be composted in the container,
- having in its lower part an openable hatch (3) for removing composted material from the container, and
- 10 - containing an air tube system (4) for guiding air in among the material to be composted in the container, characterized in that
- the air tube system (4) comprises at least two tubes (5) on different heights, extending substantially in horizontal direction and extending substantially from
- 15 side to side of the container,
- the lowermost of said tubes is connected through the wall (6) of the container with an air intake aperture (7),
- said tubes are interconnected with a connecting tube
- 20 (8),
- the lower parts of said tubes are provided with air flow holes (9), and
- the cover (2) is fitted with an exit duct (10),
- the air flowing through the air flow holes (9) of the
- 25 tubes (5) and through the material to be composted upward and through the exit duct (10) out from the container, while the material to be composted runs, supported by the transverse tubes, in controlled manner downward as the combustion of the material progresses.
- 30 2. Compost maker according to claim 1, characterized in that the compost maker comprises at least two side-by-side tubes (5) located substantially in the same plane.
3. Compost maker according to claim 1, characterized in that the connecting tube (8) is a substantially vertically directed duct connecting with each
- 35 other the tubes (5) lying in different planes.

WO 93/16018

PCT/FI93/00053

9

4. Compost maker according to any one of claims 1-3, characterized in that the air intake aperture (7) comprises an adjustable valve.

5. Compost maker according to any one of claims 1-4, characterized in that the exit duct (10) comprises an adjustable valve.

6. Compost maker according to any one of claims 1-5, characterized in that the transverse tubes (5) are oval of their cross section, in such placement that they are broader in horizontal direction and narrower in vertical direction.

7. Compost maker according to any one of claims 1-6, characterized in that the transverse tubes (5) are curved and at lower elevation at their ends than in the centre.

8. Compost maker according to any one of claims 1-7, characterized in that the transverse tubes (5) rest with their ends on an annular support which is carried by the inner shell of the container.

9. Compost maker according to claim 8, characterized in that the annular support and the transverse tubes together constitute air ducts through which the air can flow in among the material to be composted.

10. Compost maker according to claim 8 or 9, characterized in that the inner shell of the container comprises bosses or equivalent projections on which the annular support or the transverse tubes rest.

WO 93/16018

PCT/FI93/00053

1/1




Fig. 1




Fig. 2

1

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 93/00053

A. CLASSIFICATION OF SUBJECT MATTER

IPC5: C05F 17/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC5: C05F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	DE, C2, 3802499 (NEUMANN, GEORG), 2 May 1991 (02.05.91), figures 1,4, claims 1,8 --	1-4
Y	CH, A5, 632227 (FIRMA HANS KÜBLER), 30 Sept 1982 (30.09.82), figure 2, claim 1 --	1-4
A	DE, A, 2241603 (AKTIEBOLAGET ELECTROLUX), 15 March 1973 (15.03.73), figures 2-4 -----	1

☐ Further documents are listed in the continuation of Box C.
 ☒ See patent family annex.

* Special categories of cited documents:	* "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
* "A" document defining the general state of the art which is not considered to be of particular relevance	* "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
* "E" earlier document but published on or after the international filing date	* "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
* "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	* "&" document member of the same patent family
* "O" document referring to an oral disclosure, use, exhibition or other means	
* "P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search	Date of mailing of the international search report
---	--

25 May 1993

27 -05- 1993

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer
Bo Bergström
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

Information on patent family members

30/04/93

International application No.

PCT/FI 93/00053

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE-C2- 3802499	02/05/91	DE-A, C- 3844737 DE-U- 8707175	20/09/90 09/07/87
CH-A5- 632227	30/09/82	DE-A- 2709715 FR-A, B- 2382418	07/09/78 29/09/78
DE-A- 2241603	15/03/73	FR-A- 2151410	13/04/73